

4874464

60175000
s53354b

**Global Parts Order Processing
Material Safety Data Sheet
MORAN ST. CLAIR CHRYSLER JEEP**

June 6, 2012
11:42

C H R Y S L E R
HAZARD COMMUNICATION SHEET

120785 PART/COMMTY CD: 04874464
PREPARATION DATE: 10-29-04 STNDRD: N/AV SUPPLIER: 37637 MFGR: 03500
OSHA HAZ: YES HAZWOPER HAZ: YES CONS PROD/HAZ SUB: YES

*** SECTION 01 - PRODUCT INFORMATION ***

MFG BY: PART SALES & SERVICE CHRYSLER
26311 LAWRENCE AVE CENTERLINE MI 48015
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888
DIST BY: PART SALES & SERVICE CHRYSLER
26311 LAWRENCE AVE CENTERLINE MI 48015
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888
CHRYSLER INDUSTRIAL HYGIENE: 248-512-8260 AFTER HOURS: 248-576-8888
BRAND NAME: MOPAR TRANSMISSION LUBRICANT - NV-3500
MFG ID : N/AV
DESCRIPTION: FLUID-TRANSMISSION

*** SECTION 02 - INGREDIENTS ***

HAZARDOUS INGREDIENTS: PERCENT
COMM NAME / CAS NO & CHEM NAME: BY WGT OSHA ACGIH CHRYS UNITS NOTATIONS
EXISTING INGREDIENTS
PARAFFINIC PROCESS OIL 60-100 W 5 5 5 MG/M3
064742-65-0A DISTILLATES (PETROLE L N/AP 10 10
DISTILLATES (PETROLEUM), SOLVENT- 1-5 W 5 5 5 MG/M3
064741-97-5A DISTILLATES (PETROLE L N/AP 10 10
PARAFFINIC PROCESS OIL 1-5 W 5 5 5 MG/M3
064742-54-7A DISTILLATES (PETROLE L N/AP 10 10
(C8-C16) ALKYL BENZENE 10-30 W N/AV N/AV N/AV N/AV
068648-87-3 BENZENE, C10-16-ALKY
2-PROPENOIC ACID, 2-METHYL-, DODE 5-10 W N/AV N/AV N/AV N/AV
030795-64-3 2-PROPENOIC ACID, 2-
OIL-SOLUBLE PETROLEUM SULFONATE, 5-10 W N/AV N/AV N/AV N/AV
061789-87-5 SULFONIC ACIDS, PETR
DIALKYL (C1-C14) DITHIOPHOSPHORIC A 1-5 W N/AP N/AP N/AP N/AP
068649-42-3 PHOSPHORODITHIOIC AC T
GENERIC DESC: MIXTURE(S) OF THE FOLLOWING: PETROLEUM DISTILLATE(S), AROMATIC
HYDROCARBON(S) AND ESTER(S).

*** SECTION 03 - PHYSICAL DATA ***

BOILING POINT : N/AV SOLUB IN WATER: NEGLIGIBLE (< 0.1%)
VAPOR PRESSURE: N/AP MM HG ATN/AV EVAP. RATE: N/AP REF: N/AP
VAPOR DENSITY : N/AP AT N/AV SPECIFIC GRAVITY: 0.892 AT N/AP
PH AT FULL STRENGTH: N/AP PH AT REC. DILUT: N/AV

**Global Parts Order Processing
Material Safety Data Sheet
MORAN ST. CLAIR CHRYSLER JEEP**

%VOLATILE BY VOL : N/AP VOLATILE ORGANIC COMP: N/AP N/AP
ODOR THRESHOLD: N/AV PPM FOR % POPULATION
FREEZING POINT: N/AV COEFF. OF WATER/OIL DIST: N/AV
APPEARANCE & ODOR: APPEARANCE: DARK..... APPEARANCE: PALE..... STATE:
LIQUID..... ODOR: PETROLEUM.....

*** SECTION 04 - FIRE AND EXPLOSION DATA ***

FLASH POINT: 305 F COC IGN TEMP: N/AV LEL: N/AV UEL: N/AV

SPECIAL FIRE & EXPLOSION HAZARDS:

MAY PRODUCE TOXIC THERMAL DECOMPOSITION PRODUCTS. WILL MAKE FLOORS VERY SLIPPERY. SPREAD AREA WITH SAND OR OTHER GRITTY MATERIAL.

EXTINGUISHING MEDIA:

WATER FOG, DRY CHEMICAL, FOAM OR CARBON DIOXIDE. WATER OR FOAM MAY CAUSE FROTHING.

SPECIAL FIREFIGHTING PROCEDURES:

AVOID BREATHING VAPOR OR FUMES. USE SELF-CONTAINED BREATHING APPARATUS. USE PROTECTIVE CLOTHING. USE WATER TO COOL FIRE EXPOSED CONTAINERS.

SENSITIVE TO MECHANICAL IMPACT?: NO SENSITIVE TO STATIC DISCHARGE?: NO

HAZARDOUS COMBUSTION PRODUCTS:

CARBON MONOXIDE AND CARBON DIOXIDE, ALDEHYDES, KETONES AND OXIDES OF PHOSPHORUS.

FLAME PROJECTION: N/AV

*** SECTION 05 - HEALTH HAZARD DATA ***

EFFECTS OF OVEREXPOSURE - ACUTE & CHRONIC:

<<---INHALATION--->> HIGH CONCENTRATIONS OF VAPOR AND/OR MIST MAY PRODUCE THE FOLLOWING: ACUTE NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY HEADACHE, DIZZINESS, STAGGERING, CONFUSION, UNCONSCIOUSNESS OR COMA. MAY BE IRRITATING TO EYES, NOSE, AND THROAT.. SYMPTOMS ARE MORE LIKELY TO OCCUR IN POORLY VENTILATED AREAS. <<---SKIN CONTACT--->> ACUTE EXPOSURE MAY PRODUCE THE FOLLOWING: MINOR IRRITATION. IF SKIN IS MOIST OR WET, CONTACT MAY PRODUCE THE FOLLOWING: SWELLING AND MILD ERYTHEMA (REDDENING OF THE SKIN). MAY PRODUCE THE FOLLOWING: SEVERE IRRITATION. <<---EYE CONTACT--->> VAPOR AND/OR LIQUID MAY PRODUCE THE FOLLOWING: IRRITATION AND CONJUNCTIVITIS (AN INFLAMED EYE). <<---INGESTION--->> LARGE QUANTITIES-MAY CAUSE UPSET STOMACH, NAUSEA, VOMITING AND DIARRHEA. <<---SPECIAL TOXICITY--->> STUDIES OF LABORATORY ANIMALS HAVE SHOWN THAT COMPONENTS OF THIS PRODUCT MAY CAUSE THE FOLLOWING: LIVER DAMAGE. COMPONENTS HAVE BEEN SHOWN TO CAUSE CANCER IN ANIMALS. IS A SUSPECTED CARCINOGEN, BUT ANIMAL STUDIES HAVE NOT YET SHOWN DEFINITE RESULTS. <<---MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY THIS PRODUCT--->> SKIN DISORDERS.

EMERGENCY FIRST AID PROCEDURES:

<<---INHALATION--->> REMOVE TO FRESH AIR AT ONCE. IF PULMONARY SYMPTOMS DEVELOP, CONSULT A PHYSICIAN. <<---SKIN CONTACT--->> WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. IF CONDITION PERSISTS, CONSULT A

**Global Parts Order Processing
Material Safety Data Sheet
MORAN ST. CLAIR CHRYSLER JEEP**

PHYSICIAN. <<---EYE CONTACT--->> RINSE EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER, OCCASIONALLY LIFTING BOTH UPPER AND LOWER LIDS. CONTINUE FOR 15 MINUTES. CONTACT A PHYSICIAN. <<---INGESTION--->> DO NOT INDUCE VOMITING-CALL PHYSICIAN IMMEDIATELY. DRINK LARGE QUANTITIES OF WATER.

*** SECTION 06 - REACTIVITY DATA ***

STABILITY: STABLE

CONDITIONS TO AVOID:

HIGH TEMPERATURE.

MATERIALS TO AVOID:

STRONG OXIDIZING AGENTS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

POLYMERIZATION CONDITIONS TO AVOID:

POLYMERIZATION WILL NOT OCCUR.

HAZARDOUS DECOMPOSITION PRODUCTS:

CARBON MONOXIDE AND CARBON DIOXIDE, ALDEHYDES, HYDROCARBONS AND OXIDES OF PHOSPHORUS.

*** SECTION 07 - SPILL OR LEAK PROCEDURES ***

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

AVOID BREATHING VAPORS. VENTILATE AREA. WEAR RESPIRATORY PROTECTION. WEAR PROTECTIVE CLOTHING. CONTAIN WITH DIKE. ABSORB ON AN INERT MATERIAL. SHOVEL INTO STORAGE CONTAINERS. DO NOT FLUSH INTO SEWER SYSTEM.

WASTE DISPOSAL METHODS:

DISPOSE OF IN A MANNER CONSISTENT WITH STATE, PROVINCIAL, LOCAL, AND FEDERAL REGULATIONS.

*** SECTION 08 - SPECIAL PROTECTION ***

RESPIRATORY PROTECTION:

THE FOLLOWING MAY BE NEEDED IF SIGNIFICANT VAPORS OR MIST ARE GENERATED:

ORGANIC VAPOR RESPIRATOR OR AIR-SUPPLIED RESPIRATOR.

VENTILATION TYPE:

TO MAINTAIN THE TLV, THE FOLLOWING MAY BE NEEDED: GOOD GENERAL VENTILATION AND LOCAL EXHAUST VENTILATION.

PROTECTIVE GLOVES:

RECOMMENDED. NEOPRENE GLOVES OR NITRILE RUBBER GLOVES.

EYE PROTECTION:

RECOMMENDED. SAFETY GLASSES WITH SIDE SHIELDS OR USE CHEMICAL GOGGLES OR FACESHIELD UNDER NORMAL CONDITIONS. USE BOTH CHEMICAL GOGGLES AND FACESHIELD IF LIKELY TO BE SPLASHED.

OTHER PROTECTIVE EQUIPMENT:

TO AVOID PROLONGED SKIN CONTACT, USE THE FOLLOWING: CLOTHING (SAME MATERIAL AS GLOVES), APRON (SAME MATERIAL AS GLOVES) OR WEAR LONG SLEEVES.

**Global Parts Order Processing
Material Safety Data Sheet
MORAN ST. CLAIR CHRYSLER JEEP**

*** SECTION 09 - SPECIAL PRECAUTIONS ***

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE:

STORE IN A COOL, DRY PLACE. AVOID USING OR STORING AT HIGH TEMPERATURES.
AVOID CONTAMINATION WITH WATER. STORE SEPARATE FROM INCOMPATIBLE MATERIALS.

OTHER PRECAUTIONARY MEASURES:

AVOID BREATHING VAPOR. AVOID SKIN CONTACT. AVOID EYE CONTACT. AVOID
INGESTION. DO NOT SMOKE OR EAT WHEN HANDLING THIS SUBSTANCE; WASH THOROUGHLY
AFTER USING. REMOVE CONTAMINATED CLOTHING AND LAUNDRY BEFORE REUSE. MAINTAIN
GOOD HOUSEKEEPING AND HYGIENIC PRACTICES.

*** SECTION 10 - WASTE LABELING INFORMATION ***

DOT LABELING INFORMATION (49 CFR 100-199)

ID#: N/AP ERG#: HAZARD CLASS - PRMY: N/AP PACKING GROUP: N/AP
NOT HAZARDOUS PER DOT REGULATIONS

RCRA INFORMATION (40 CFR 122-124, 260-265)

WASTE CODE(S)/HSD: | MICH: 003D

THE ABOVE INFORMATION IS BASED ON DATA PROVIDED BY SUPPLIERS AND IS NOT BASED
ON LABORATORY ANALYSIS. TESTING IS RECOMMENDED.