

4918007

60175000  
s53354b

**Global Parts Order Processing  
Material Safety Data Sheet  
MORAN ST. CLAIR CHRYSLER JEEP**

June 6, 2012  
11:13

C H R Y S L E R  
HAZARD COMMUNICATION SHEET

25431 PART/COMMTY CD: 04318017  
PREPARATION DATE: 06-18-03 STNDRD: N/AV SUPPLIER: 12091 MFGR: 03500  
OSHA HAZ: YES HAZWOPER HAZ: YES CONS PROD/HAZ SUB: YES

\*\*\* SECTION 01 - PRODUCT INFORMATION \*\*\*

MFG BY: PART SALES & SERVICE CHRYSLER  
26311 LAWRENCE AVE CENTERLINE MI 48015  
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888  
DIST BY: PART SALES & SERVICE CHRYSLER  
26311 LAWRENCE AVE CENTERLINE MI 48015  
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888  
CHRYSLER INDUSTRIAL HYGIENE: 248-512-8260 AFTER HOURS: 248-576-8888  
BRAND NAME: MOPAR LEATHER, RUBBER & VINYL PROTECTOR  
MFG ID : N/AV  
DESCRIPTION: CLEANER-LEATHER AND VINYL

\*\*\* SECTION 02 - INGREDIENTS \*\*\*

HAZARDOUS INGREDIENTS: PERCENT  
COMM NAME / CAS NO & CHEM NAME: BY WGT OSHA ACGIH CHRYS UNITS NOTATIONS  
\*\*\*EXISTING INGREDIENTS\*\*\*  
ISOPROPYL ALCOHOL 10-30 W 400 200 400 PPM  
000067-63-0 2-PROPANOL (9CI) L 500 400 500  
DIPROPYLENE GLYCOL METHYL ETHER 5-10 W 100 100 100 PPM S  
034590-94-8 PROPANOL, 1(OR 2)-(2 L 150 150 150  
METHACRYLIC ACID METHYL ESTER, PO 5-10 W N/AP N/AP N/AP N/AP  
009011-14-7 2-PROPENOIC ACID, 2-  
WATER 30-60 W N/AP N/AP N/AP N/AP  
007732-18-5 WATER (8CI9CI)  
GENERIC DESC: VINYL DRESSING- AQUEOUS MIXTURE OF ALCOHOLS, SURFACTANTS AND  
RESINS.

\*\*\* SECTION 03 - PHYSICAL DATA \*\*\*

BOILING POINT : 198 F SOLUB IN WATER: COMPLETE ( IN ALL PROPOR  
VAPOR PRESSURE: N/AV EVAP. RATE: N/AV REF: N/AP  
VAPOR DENSITY : 1.000 AT N/AV SPECIFIC GRAVITY: 0.960 AT N/AV  
PH AT FULL STRENGTH: N/AV PH AT REC. DILUT: N/AV  
%VOLATILE BY VOL : N/AV VOLATILE ORGANIC COMP: N/AV N/AV  
ODOR THRESHOLD: N/AV PPM FOR % POPULATION  
FREEZING POINT: N/AV COEFF. OF WATER/OIL DIST: N/AV  
APPEARANCE & ODOR: COLOR: WHITE..... APPEARANCE: OPAQUE..... STATE:  
LIQUID....., ODOR: ALCOHOL.....

**Global Parts Order Processing  
Material Safety Data Sheet  
MORAN ST. CLAIR CHRYSLER JEEP**

\*\*\* SECTION 04 - FIRE AND EXPLOSION DATA \*\*\*

FLASH POINT: N/AP N/AP IGN TEMP: N/AP LEL: N/AV UEL: N/AV

SPECIAL FIRE & EXPLOSION HAZARDS:

IGNITES.

EXTINGUISHING MEDIA:

CARBON DIOXIDE, FOAM AND DRY CHEMICAL B.

SPECIAL FIREFIGHTING PROCEDURES:

USE WATER TO COOL FIRE EXPOSED CONTAINERS. USE PROTECTIVE CLOTHING. USE

SELF-CONTAINED BREATHING APPARATUS. AVOID BREATHING VAPOR OR FUMES.

SENSITIVE TO MECHANICAL IMPACT?: N/AV SENSITIVE TO STATIC DISCHARGE?: N/AV

HAZARDOUS COMBUSTION PRODUCTS:

N/AV

FLAME PROJECTION: N/AV

\*\*\* SECTION 05 - HEALTH HAZARD DATA \*\*\*

EFFECTS OF OVEREXPOSURE - ACUTE & CHRONIC:

<<---INGESTION--->> MAY BE HARMFUL IF SWALLOWED. WILL PRODUCE THE FOLLOWING: NAUSEA, VOMITING, DIARRHEA, AND ABDOMINAL CRAMPS. <<---EYE CONTACT--->> WILL PRODUCE THE FOLLOWING: IRRITATION AND TEARING. WILL PRODUCE THE FOLLOWING: SEVERE IRRITATION. <<---SKIN CONTACT--->> MAY PRODUCE THE FOLLOWING: DEFATTING AND DRYING OF SKIN. MAY BE ABSORBED THROUGH SKIN. <<---INHALATION--->> MAY PRODUCE THE FOLLOWING: IRRITATION OF UPPER RESPIRATORY TRACT. HIGH CONCENTRATIONS--CAUSES NARCOSIS.

EMERGENCY FIRST AID PROCEDURES:

<<---INGESTION--->> DO NOT INDUCE VOMITING-CALL PHYSICIAN IMMEDIATELY.  
<<---EYE CONTACT--->> RINSE EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER, OCCASIONALLY LIFTING BOTH UPPER AND LOWER LIDS. CONTINUE FOR 15 MINUTES. CONTACT A PHYSICIAN. <<---SKIN CONTACT--->> WASH WITH SOAP AND WATER.  
<<---INHALATION--->> REMOVE TO FRESH AIR AT ONCE. CONTACT A PHYSICIAN.

\*\*\* SECTION 06 - REACTIVITY DATA \*\*\*

STABILITY: STABLE

CONDITIONS TO AVOID:

SPARKS OR OPEN FLAME OR HIGH TEMPERATURE.

MATERIALS TO AVOID:

COMBUSTIBLE MATERIALS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

POLYMERIZATION CONDITIONS TO AVOID:

POLYMERIZATION WILL NOT OCCUR.

HAZARDOUS DECOMPOSITION PRODUCTS:

NOT AVAILABLE.

\*\*\* SECTION 07 - SPILL OR LEAK PROCEDURES \*\*\*

**Global Parts Order Processing  
Material Safety Data Sheet  
MORAN ST. CLAIR CHRYSLER JEEP**

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

DILUTE WITH WATER AND FLUSH INTO SEWER SYSTEM. AVOID BREATHING VAPORS.  
VENTILATE AREA.

WASTE DISPOSAL METHODS:

DISPOSE OF IN A MANNER CONSISTENT WITH STATE, PROVINCIAL, LOCAL, AND  
FEDERAL REGULATIONS. DISPOSE OF IN A LANDFILL.

-----  
\*\*\* SECTION 08 - SPECIAL PROTECTION \*\*\*  
-----

RESPIRATORY PROTECTION:

ORGANIC VAPOR RESPIRATOR.

VENTILATION TYPE:

GOOD GENERAL VENTILATION AND LOCAL EXHAUST VENTILATION.

PROTECTIVE GLOVES:

RECOMMENDED. RUBBER GLOVES.

EYE PROTECTION:

RECOMMENDED. CHEMICAL GOGGLES.

OTHER PROTECTIVE EQUIPMENT:

APRON (SAME MATERIAL AS GLOVES). A SAFETY SHOWER MAY BE NEEDED FOR  
EMERGENCY SITUATIONS. AND AN EYE WASH MAY BE NEEDED FOR EMERGENCY  
SITUATIONS.. THIS EQUIPMENT MAY BE NEEDED FOR EMERGENCY SITUATIONS.

-----  
\*\*\* SECTION 09 - SPECIAL PRECAUTIONS \*\*\*  
-----

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE:

KEEP FROM HEAT, SPARK OR OPEN FLAMES. STORE IN A WELL VENTILATED AREA.

OTHER PRECAUTIONARY MEASURES:

AVOID BREATHING VAPOR. AVOID SKIN CONTACT. AVOID EYE CONTACT. AVOID  
INGESTION. DO NOT SMOKE OR EAT WHEN HANDLING THIS SUBSTANCE; WASH THOROUGHLY  
AFTER USING. REMOVE CONTAMINATED CLOTHING AND LAUNDRER BEFORE REUSE.

-----  
\*\*\* SECTION 10 - WASTE LABELING INFORMATION \*\*\*  
-----

DOT LABELING INFORMATION (49 CFR 100-199)

ID#: N/AP ERG#: HAZARD CLASS - PRMY: N/AP PACKING GROUP: N/AP

NOT HAZARDOUS PER DOT REGULATIONS

RCRA INFORMATION (40 CFR 122-124, 260-265)

WASTE CODE(S)/HZD: | MICH: N/AP

THE ABOVE INFORMATION IS BASED ON DATA PROVIDED BY SUPPLIERS. TESTING IS NOT  
NEEDED