Permatex, Inc.

10 Columbus Blvd. Hartford, CT 06106 USA Telephone: 1-87-Permatex

(877) 376-2839

Emergency: 800-255-3924

International Emergency: 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: B FORCE HYDRAULIC JACK OIL 32 FL.OZ

Item No: 80051
Product Type: Lubricant

| 2. COMPOSITION/INFORMATION ON INGREDIENTS | | | |
|---|---------|----------------|------------|
| Component | Weight% | ACGIH TLV: TWA | OSHA PEL: |
| VEGETABLE OILS, ADDITIVES | 100 | Not listed | Not Listed |
| NON HAZARDOUS | | | |

3. HAZARDS IDENTIFICATION

Toxicity: Prolonged skin contact may result in dermatitis in sensitive individuals. At elevated temperatures may

cause irritation of the respiratory tract.

Primary Routes of Entry:

Signs and Symptoms of Exposure:

cause irritation of the respiratory tract.

Eye and skin contact, ingestion, inhalation

Overexposure may cause eye and skin redness.

Medical Conditions Recognized as

Being Aggravated by Exposure:

None known.

4. FIRST AID MEASURES

Ingestion: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.

Inhalation: Move to fresh air in case of accidental inhalation of vapours.

Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical

attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): >400°F COC

Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.

Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus. Product floats

on water.

Hazardous Products of Combustion: Oxides of carbon, Aldehydes

Unusual Fire/Explosion Hazards: None.

Lower Explosive Limit: Not determined.
Upper Explosive Limit: Not determined.

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until

disposal.

7. HANDLING AND STORAGE

Storage: Store in a cool, dry area.

Handling: Wash thoroughly after handling.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eves: Safety glasses.

Skin:Neoprene or nitrile gloves recommended.Ventilation:General ventilation is usually adequate.Respiratory Protection:Not required under normal use.

Product Name: B FORCE HYDRAULIC JACK OIL 32 Item No: 80051

FL.OZ

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Amber liquid Odor: Amber MILD

Boiling Point: Not determined pH: Not apply

Solubility in Water:

Specific Gravity: 0.9 @ 15°C

VOC Content(Wt.%):

Vapor Pressure:Not determinedVapor Density (Air=1):Not determinedEvaporation Rate:Not determined

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions

Hazardous Polymerization:Will not occur.Incompatabilities:Strong oxidizers

Conditions to Avoid: Heat.

Hazardous Products of Combustion: Oxides of carbon, Aldehydes

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.

US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

Comments: Ultimate biodegradation Pw1 >60% within 28 days as per ASTM D-5864 Aerobic Aquatic Biodegradation

of Lubricants.

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name: Unrestricted Hazard Class: None UN/ID Number: None Marine Pollutant: None

IATA

Proper Shipping Name: Not regulated Class or Division: None UN/ID Number: None

IMDG

Proper Shipping: Unrestricted None UN Number: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

Product Name: B FORCE HYDRAULIC JACK OIL 32 <u>Item No:</u> 80051

FL.OZ

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0.
Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn. HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety Revision Date: February/29/2008

Company: Permatex. Inc. 10 Columbus Blvd. Hartford, CT USA 06106 Revision

Number:

Telephone No.: 1-87-Permatex (877) 376-2839