Material Safety Data Sheet



1. Product and company identification

Product name

Castrol AP Gear 80W-90

MSDS#

460826

Historic MSDS #:

0000002626

Code

460826-US06 US13

Product use

Gear lubricant

roduct use Gear iunicar

For specific application advice see appropriate Technical Data Sheet or consult our company

representative.

Manufacturer

BP Lubricants USA Inc. 1500 Valley Road Wayne, NJ 07470

Telephone: (973) 633-2200 Telecopier: (973) 633-7475

EMERGENCY HEALTH

INFORMATION:

1 (800) 447-8735

Outside the US: +1 703-527-3887 (CHEMTREC)

EMERGENCY SPILL

INFORMATION:

1 (800) 424-9300 CHEMTREC (USA)

OTHER PRODUCT

1 (866) 4 BP - MSDS

INFORMATION

(866-427-6737 Toll Free - North America)

email: bpcares@bp.com

2. Hazards identification

Physical state

Liquid.

Color

Amber.

Emergency overview

CAUTION!

MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION.

Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash

thoroughly after handling.

Routes of entry

Dermal contact. Eye contact. Inhalation. Ingestion.

Potential health effects

Eyes

May cause eye irritation.

Skin

May cause skin irritation. Prolonged or repeated contact can defat the skin and lead to irritation

and/or dermatitis.

Inhalation

May cause respiratory tract irritation.

Ingestion

Ingestion may cause gastrointestinal irritation and diarrhea.

See toxicological information (section 11)

Product name Castrol AP Gear 80W-90

Product code

460826-US06 US13 Page: 1/6

Version 3

Date of issue 06/29/2009.

Format US

Language ENGLISH.

(US)

3. Composition/information on ingredients

 Ingredient name
 CAS #
 %

 Base oil - highly refined
 Varies
 90 - 95

 Olefin sulfide
 68937-96-2
 1 - 5

 Base oil - highly refined
 72623-86-0
 1 - 5

4. First aid measures

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical

attention if symptoms occur.

Skin contact Immediately wash expos d skin with soap and water. Remove contaminated clothing and shoes.

Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if

symptoms occur.

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. Never give anything by

mouth to an unconscious person. If potentially dangerous quantities of this material have been

swallowed, call a physician immediately. Get medical attention if symptoms occur.

5. Fire-fighting measures

Flash point Open cup: 216°C (420.8°F) [Cleveland.]

Fire/explosion hazards In a fire or if heated, a pressure increase will occur and the container may burst.

Extinguishing media

Suitable Use an extinguishing agent suitable for the surrounding fire.

Not suitable Do not use water jet.

Fire-fighting procedures Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

No action shall be taken involving any personal risk or without suitable training.

Hazardous combustion

products

Combustion products may include the following:

phosphorus oxides

carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

sulfur oxides (SO₂, SO₃ etc.) nitrogen oxides (NO, NO₂ etc.)

Protective clothing (fire) Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus

(SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions No action shall be taken involving any personal risk or without suitable training. Keep unnecessary

and unprotected personnel from entering. Do not touch or walk through spilled material. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see

section 8).

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Inform the relevant authorities if the product has caused environmental pollution (sewers,

waterways, soil or air).

Methods for cleaning up

Large spill Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent

entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal

contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

Note: see section 1 for emergency contact information and section 13 for waste disposal.

Product name Castrol AP Gear 80W-90

Product code

460826-US06 US13 Page: 2/6

Version 3 Date of issue 06/29/2009.

Format US

Language ENGLISH.

(US)

Small spill

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if watersoluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Handling

Put on appropriate personal protective equipment (see section 8). Workers should wash hands and face before eating, drinking and smoking. Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate.

Storage

Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Occupational exposure limits

Ingredient name Occupational exposure limits

Base oil - highly refined ACGIH (United States).

STEL: 10 mg/m³ 15 minute(s). Form: Mineral oil, mist TWA: 5 mg/m³ 8 hour(s). Form: Mineral oil, mist

OSHA (United States).

TWA: 5 mg/m3 8 hour(s). Form: Mineral oil, mist

Base oil - highly refined ACGIH (United States).

STEL: 10 mg/m³ 15 minute(s). Form: Mineral oil, mist TWA: 5 mg/m³ 8 hour(s). Form: Mineral oil, mist

OSHA (United States).

TWA: 5 mg/m³ 8 hour(s). Form: Mineral oil, mist

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Some states may enforce more stringent exposure limits.

Control Measures Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist,

use process enclosures, local exhaust ventilation or other engineering controls to keep worker

exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before eating,

smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before

reusing.

Personal protection

Eyes Avoid contact with eyes. Safety glasses with side shields or chemical goggles.

Skin and body Avoid contact with skin and clothing. Wear suitable protective clothing.

Respiratory Use adequate ventilation. In accordance with good industrial hygiene and safety work practices,

airborne exposures should be controlled to the lowest extent practicable.

Hands The correct choice of protective gloves depends upon the chemicals being handled, the conditions

of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and

with a full assessment of the working conditions.

Consult your supervisor or S.O.P. for special handling instructions.

Product name Castrol AP Gear 80W-90

Product code

460826-US06 US13 Page: 3/6

Version 3 Date of issue 06/29/2009.

Format US

Language ENGLISH.

(US)

9. Physical and chemical properties

Physical state

Liquid.

Color

Amber.

Flash point

Open cup: 216°C (420.8°F) [Cleveland.]

Specific gravity

0.887

Viscosity

Kinematic: 147.1 mm²/s (147.1 cSt) at 40°C

Kinematic: 14.8 mm²/s (14.8 cSt) at 100°C

SUS: 771 SUS at 37.8°C

Solubility

insoluble in water.

10. Stability and reactivity

Stability and reactivity

The product is stable.

Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Avoid all possible sources of ignition (spark or flame).

Conditions to avoid Incompatibility with various substances

Reactive or incompatible with the following materials: oxidizing materials.

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition products should not be

produced.

Hazardous polymerization

Under normal conditions of storage and use, hazardous polymerization will not occur.

11. Toxicological information

Other Toxicity Data

Contains low concentration of olefin sulfide. Based on animal studies at high concentration may

cause allergic skin reactions with repeated exposure.

Other information

Potential chronic health effects

Carcinogenicity

No known significant effects or critical hazards.

12. Ecological information

Ecotoxicity

No testing has been performed by the manufacturer.

13. Disposal considerations

Waste information

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

NOTE: The generator of waste has the responsibility for proper waste identification (based on characteristic(s) or listing), transportation and disposal

Product name Castrol AP Gear 80W-90

Product code

460826-US06 US13 Page: 4/6

Version 3 D

Date of issue 06/29/2009.

Format US

Language ENGLISH.

(US)

14. Transport information

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

15. Regulatory information

U.S. Federal Regulations

United States inventory (TSCA 8b)

All components are listed or exempted.

TSCA 12(b) one-time export: mequinol; p-Xylene; Naphthalene

SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found.

SARA 302/304/311/312 hazardous chemicals: No products were found.

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Castrol AP

Gear 80W-90: Immediate (acute) health hazard

SARA 313

Form R - Reporting requirements

This product does not contain any hazardous ingredients at or above regulated thresholds.

Supplier notification **CERCLA Sections**

This product does not contain any hazardous ingredients at or above regulated thresholds.

102a/103 Hazardous Substances (40 CFR Part 302.4):

CERCLA: Hazardous substances.: Cadmium: 10 lbs. (4.54 kg); lead: 10 lbs. (4.54 kg); Arsenic: 1 lb. (0.454 kg); Ethyl acrylate: 1000 lbs. (454 kg); p-Xylene: 100 lbs. (45.4 kg); cumene: 5000 lbs. (2270 kg); Benzene: 10 lbs. (4.54 kg); Toluene: 1000 lbs. (454 kg); xylene: 100 lbs. (45.4 kg);

Naphthalene: 100 lbs. (45.4 kg);

State regulations

Massachusetts Substances

None of the components are listed.

New Jersey Hazardous Substances

None of the components are listed.

Pennsylvania RTK **Hazardous Substances**

None of the components are listed.

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer. Naphthalene; Ethyl acrylate; Arsenic

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Toluene

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Cadmium; lead; Benzene

Inventories

Canada inventory All components are listed or exempted. Europe inventory All components are listed or exempted.

Australia inventory (AICS) Not determined. China inventory (IECSC) Not determined. Japan inventory (ENCS) Not determined.

Korea inventory (KECI) All components are listed or exempted. Philippines inventory

(PICCS)

All components are listed or exempted.

Product name Castrol AP Gear 80W-90 Version 3 Date of issue 06/29/2009. Product code 460826-US06 US13 Page: 5/6

Format US

Language ENGLISH.

(US)

16. Other information

Label requirements

CAUTION !

MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION.

HMIS® Rating:

Health

National Fire

Flammability 1

Protection

Physical 0 Hazard

Х

Association (U.S.A.)

Fire hazard

Health

O Instability

Specific hazard

History

Date of issue

06/29/2009.

Personal

protection

Date of previous issue

06/15/2006.

Prepared by

Product Stewardship

Notice to reader

NOTICE: This Material Safety Data Sheet is based upon data considered to be accurate at the time of its preparation. Despite our efforts, it may not be up to date or applicable to the circumstances of any particular case. We are not responsible for any damage or injury resulting from abnormal use, from any failure to follow appropriate practices or from hazards inherent in the nature of the product.

Product name Castrol AP Gear 80W-90

Product code

460826-US06 US13 Page: 6/6

Version 3

Date of issue 06/29/2009.

Format US

Language ENGLISH.

(US)