

MSDS Material Safety Data Sheet

The Blaster Corporation



ATC - Air Tool Conditioner

MSDS Number: ATC Aerosol

Revision Date: 02/17/2011

Page 1 of 7

1 PRODUCT AND COMPANY IDENTIFICATION

Product Name: **ATC - Air Tool Conditioner**
 Revision Date: 02/17/2011
 MSDS Number: ATC Aerosol
 Product Code: 8-ATC-S, 16-ATC, ATC-TS

Manufacturer: The Blaster Corporation
 8500 Sweet Valley Drive
 Valley View, Ohio 44125

(216) 901-5800
 (216) 901-5801 fax
 www.blasterproducts.com

24 Hour emergency contact: Chemtrec (800) 424-9300

2 COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS #	Percent	Exposure Limits
Zinc Alkyl Dithiophosphate	68649-42-3	1-10%	OSHA (TWA)- N/E ACGIH (TLV)- N/E
Propylene Glycol t-Butyl Ether	9003-13-8	0-10%	OSHA (TWA)- N/E ACGIH (TLV)- N/E
Isopropanol	67-63-0	10-20%	OSHA (TWA)- 400 ppm ACGIH (TWA)- 400 ppm
Petroleum Distillate (Mineral Oil)		40-55	OSHA (TWA)- 5 mg/m3 oil mist ACGIH (TWA)- 5 mg/m3 oil mist
VM&P Naphtha	8032-32-4	20-30%	OSHA (TWA)- 300 ppm ACGIH (TWA)- 300 ppm
Carbon Dioxide	124-38-9	0-3%	OSHA (TWA)- 5000 ppm ACGIH (TWA)- 5000 ppm

3 HAZARDS IDENTIFICATION

Route of Entry: Eyes, skin, inhalation, ingestion

Target Organs:

Inhalation: Tests on similar material indicate the possibility of the following symptoms: headache, nasal and respiratory irritation, nausea, drowsiness, breathlessness, fatigue, central nervous system depression, convulsions, and loss of consciousness.

Skin Contact: Tests on similar materials indicate acute irritation is expected to occur upon short-term

MSDS Material Safety Data Sheet

The Blaster Corporation



ATC - Air Tool Conditioner

MSDS Number: ATC Aerosol

Revision Date: 02/17/2011

Page 2 of 7

Eye Contact: exposure, chronic dermatitis on prolonged contact. Tests on similar materials suggest acute irritation be expected.

Ingestion: ACUTE ASPIRATION HAZARD. Tests on similar materials indicate possibility of the following symptoms: headache, nausea, drowsiness, fatigue, pneumonitis, pulmonary adema, central nervous system depression, convulsions, and loss of consciousness.

May aggravate a pre-existing skin and respiratory disorders. Personnel with pre-existing skin disorders should avoid contact with this product.

Physical Hazard: Aerosol containers are pressurized (even when empty!) Do not expose to temperatures above 120° F. Do not puncture or burn can. Failure to observe these precautions may result in rapid and violent decompression of the container producing projectiles and atomization of the liquid contents.

Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

4 FIRST AID MEASURES

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Continue to monitor. Get medical attention.

Skin Contact: Remove contaminated clothing immediately! Wash skin with soap and water. If irritation develops, seek medical attention.

Eye Contact: Flush eye(s) with water for 15 minutes. Get medical attention. If eye irritation persists, obtain medical treatment.

Ingestion: CALL PHYSICIAN IMMEDIATELY. Do not induce vomiting except at the instruction of a physician.

5 FIRE FIGHTING MEASURES

Flashpoint: 58° F (TCC)

Unusual Fire & Explosion Hazard: Level 3 Aerosols - Contents Under Pressure

Extinguishing Media: Dry chemical. Carbon dioxide, halon or foam.

6 ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedure: Leaking cans should be put into suitable container until the internal pressure has dissipated.

Waster Disposal Method: Empty aerosol cans should be punctured and drained. Can and contents can then be incinerated. Dispose of in accordance with local, state and federal regulations.

MSDS Material Safety Data Sheet

The Blaster Corporation



ATC - Air Tool Conditioner

MSDS Number: ATC Aerosol

Revision Date: 02/17/2011

Page 3 of 7

7 HANDLING AND STORAGE

Handling Precautions: Use in accordance with good industrial workplace practices. Avoid unnecessary contact. Wash thoroughly after handling. Use with good ventilation.

Storage Requirements: Store in a dry place away from excessive heat. Store containers with lids on and properly labeled.

Do not store at temperatures above 120 degrees F.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Eye wash stations and emergency showers should be immediately available.

Protective Equipment: Eyes and Face: Standard safety glasses with splash shields typically offer adequate protection. Where excessive splashing or spraying is possible, a face shield should be used.

Skin and clothing: Excessive contact should be avoided. Neoprene gloves, boots and aprons will provide adequate protection when contact cannot be avoided. Remove and wash any contaminated clothing immediately. Wash thoroughly after handling.

Respiratory: Good general ventilation should be sufficient to control airborne levels. Maintain airborne concentrations below OSHA established exposure limits of ingredients in Section 2.

Exposure Guidelines/Other: The Blaster Chemical Companies takes no responsibility for determining what measures are required for personal protection in any specific application. This information should be used with discretion.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Red viscous oily	Boiling Point:	180 F
Physical State:	Liquid	Freezing/Melting Pt.:	Not determined
Odor:	aromatic	Solubility:	nil
pH:	Not determined	Spec Grav./Density:	0.90 (water = 1)
Vapor Pressure:	Not determined		
Vapor Density:	>1 (air = 1)		

Heat Value:	Not determined
VOC:	Not determined
Evap. Rate:	>1 (NBA = 1)
Bulk Density:	Not determined
Octanol:	Not applicable
Molecular Weight:	Not determined
Particle Size:	Not applicable
Softening Point:	Not applicable
Viscosity:	Not determined
Percent Volatile:	Not determined
Sat. Vap. Concentrat.:	Not determined
Molecular Formula:	Not determined

MSDS Material Safety Data Sheet

The Blaster Corporation



ATC - Air Tool Conditioner

MSDS Number: ATC Aerosol

Revision Date: 02/17/2011

Page 4 of 7

10 STABILITY AND REACTIVITY

Stability:	This product is stable.
Conditions to avoid:	Avoid excessive heat, sources of ignition and excessive water.
Materials to avoid (incompatibility):	Avoid contact with strong oxidizing agents and strong reducing agents (strong acids or bases.) Avoid mixture with water.
Hazardous Decomposition products:	Carbon monoxide, carbon dioxide, and various hydrocarbons.
Hazardous Polymerization:	Will not occur.

11 TOXICOLOGICAL INFORMATION

• Propylene Glycol t-Butyl Ether 9003-13-8

Acute Toxicity - Lethal Doses

LC50 (Inhl) Rat > 550 PPM 4 HOURS
LD50 (Oral) Rat 3771 MG/KG BWT
LD50 (Skin) Rabbit > 2000 MG/KG BWT

Acute Toxicity - Effects

Inhalation May produce symptoms of central nervous system depression including headache, dizziness, nausea, loss of sense of balance, drowsiness, visual disturbances, unconsciousness and sense of balance, drowsiness, visual disturbances, unconsciousness and death. Ingestion High doses may cause CNS depression (fatigue, dizziness and possibly loss of concentration, with collapse, coma and death in cases of severe over-exposure). Skin Contact Not expected to be a skin absorption hazard.

Irritation

Skin Contact may cause mild skin irritation.

Eye Irritation can range from slight to severe. Neat liquid may produce severe eye irritation. A 20% solution of in water was, at most, slightly irritating to the eye. Severe irritation may result in corneal opacity, redness, inflammation of the iris and swelling of the conjunctiva.

Sensitization: Not expected to be a sensitizer.

Target Organ Effects: Eye. Skin. Central nervous system effects.

Repeated Dose Toxicity

Low inherent toxicity following repeated inhalation exposure. Effects observed in male rats that inhaled high concentrations of PTB included a species- and sex-specific kidney toxicity mediated by a-2u-globulin nephropathy, a mechanism that is not relevant to humans. Liver changes indicative of an adaptive response to metabolizing PTB were observed in rats and mice.

Reproductive Effects

No adverse effect on reproductive performance was seen in male and female rats exposed by oral gavage in a one-generation reproductive toxicity study. Very slight effects on pup body weights and survival were noted in pups from dams exposed to 1000 mg/kg bwt/day of PTB.

Developmental Effects

Results from studies in pregnant rats and rabbits demonstrate PTB is not teratogenic or fetotoxic.

Genetic Toxicity

Based on the weight of evidence, PTB is not considered to be genotoxic in vitro. A weakly mutagenic response was noted in female mice from a mouse peripheral blood micronucleus assay while male mice were negative in the same study.

Carcinogenicity

Long term inhalation exposure to PTB vapor was associated with an increased incidence of liver tumors in male and female mice and a marginally increased incidence of liver and kidney tumors in male rats. Studies suggest that the rat kidney toxicity and subsequent tumors

MSDS Material Safety Data Sheet

The Blaster Corporation



ATC - Air Tool Conditioner

MSDS Number: ATC Aerosol

Revision Date: 02/17/2011

Page 5 of 7

are due to a species and sex-specific mechanism and not relevant to humans. The weight of evidence from genotoxicity testing suggests that a non-genotoxic mechanism was most likely involved in the development of the rodent liver tumors. PTB is not classified for carcinogenicity by OSHA, NTP or the EPA. The International Agency for Research on Cancer (IARC) found inadequate human evidence and limited animal evidence of carcinogenicity for PTB and therefore was placed in IARC's Group 3 as not classifiable as to its carcinogenicity to humans.

Isopropanol

Additional Remarks Exposure can cause nausea, headache and vomiting. May be harmful by inhalation, ingestion, skin adsorption.

Eyes Irritating to eyes.

Skin Acute dermal LD50 (rabbit): 12,800 mg/kg

Inhalation Acute 4 hours LC50 (rat): 16,970 mg/l

Ingestion Acute oral LD50(rat): 5,045 mg/kg

CARCINOGENICITY

This product contains no carcinogenic substances.

VM&P Naphtha

Skin effects

May cause irritation or dermatitis with prolonged and repeated contact.

Oral effects

Tests on similar materials indicate an order of acute oral toxicity.

Inhalation effects

Acute toxicity expected on inhalation.

Medical conditions aggravated by overexposure

Dermatitis and sensitive skin - this product is not listed as carcinogenic or a potential carcinogen by the national toxicology program, by the I.A.R.C. monographs or by OSHA. Nevertheless, good industrial hygienic practices are recommended.

Petroleum Distillate (Mineral Oil)

INHALATION: Will not produce vapors unless heated to temperatures of ~300 F.°

EYE CONTACT: Irritating, but will not permanently injure eye tissue.

SKIN CONTACT: Prolonged or repeated contact may cause skin irritation.

INGESTION: Small amounts (tablespoonful) swallowed are not likely to cause injury. Larger amounts may cause nausea and vomiting. Consult a physician promptly.

CHRONIC (CANCER) INFORMATION: IARC Monographs state that when laboratory animals are exposed to severely hydrotreated oils, such as these product(s), there is insufficient evidence for cancer. Thus, these oils are Unlabeled in accordance with 29 CFR 1910.1200.

Median Lethal Dose (LD50 LC50) (Species)

Oral: Believed to be >5g/kg (rat); practically non-toxic

Inhalation: Not Determined

Dermal: Believed to be >3 g/kg (rat); practically non-toxic.

Irritation Index Estimation of Irritation (Species).

Skin: Believed to be <0.5/8.0 (rabbit); no appreciable effect

Eyes: Believed to be <15/110 (rabbit); no appreciable effect

Sensitization: Not Available

Other: None

NOTE: Some studies have linked the overexposure of "solvents" to lasting neurological effects and non-Hodgkins Lymphoma.

12

ECOLOGICAL INFORMATION

Ecological information on this product as a mixture has not been determined.

MSDS Material Safety Data Sheet

The Blaster Corporation



ATC - Air Tool Conditioner

MSDS Number: ATC Aerosol

Revision Date: 02/17/2011

Page 6 of 7

13 DISPOSAL CONSIDERATIONS

Used or unused product should be disposed of in accordance with local, state, and federal regulations. Some special regulations may exist for the disposal of empty aerosol containers.

Empty containers may contain residual pressure and contents. They should be handled with the same precautions as the product.

14 TRANSPORT INFORMATION

Dept. of Transportation (DOT):

This product, as it leaves Blaster's facilities, meets the definitions set forth in CFR 49 part 173.150c as a "consumer commodity." Allowing for certain exceptions (173.156) for domestic surface (ground) shipments.

Proper shipping name: Consumer Commodity
Hazard class: ORM-D

International (IMDT-IATA):

Proper shipping name: Aerosols, Limited Quantities
Hazard class: 2.1 Flammable Gas
UN Number: 1950

15 REGULATORY INFORMATION

Environmental Regulations

SARA 311:

Acute health:	Yes	Chronic health:	No
Fire:	Yes	Sudden release of pressure:	No
Reactive:	No		

SARA 313: Title III of the 1986 Superfund Amendments and Reauthorization Act (SARA) and 40 CFR PART 372.
Zinc Alkyl Dithiophosphate 68649-42-3

All the chemicals used in this product are TSCA listed.
Check with your local regulators to be sure all local regulations are met.

MSDS Material Safety Data Sheet

The Blaster Corporation



ATC - Air Tool Conditioner

MSDS Number: ATC Aerosol

Revision Date: 02/17/2011

Page 7 of 7

16

OTHER INFORMATION

Manufacturer's Disclaimer:

To the best of our knowledge, the information contained herein is accurate. However, neither The Blaster Chemical Companies nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists.

HMIS Ratings:

Health: 2
Fire: 3
Reactivity: 0

NFPA Ratings:

Health: 2
Fire: 3
Reactivity: 0

END OF MSDS DOCUMENT