

ASHLAND
SAFETY DATA SHEET

Page: 1
Revision Date: 03/14/2011
Print Date: 3/16/2011
MSDS Number: R0171784
Version: 2.0

NAPA® PREM PERF UFMO SAE 15W40
MOTOR OIL
NP75128

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone number	1-800-ASHLAND (1-800-274-5263)

Product name	NAPA® PREM PERF UFMO SAE 15W40 MOTOR OIL
Product code	NP75128
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, amber

WARNING! CAUSES EYE IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY THE SKIN AND CAUSE IRRITATION AND BURNS. MAY BE HARMFUL IF SWALLOWED.

Potential Health Effects

Exposure routes

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

Can cause severe eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. Can injure eye tissue.

Skin contact

May cause mild skin irritation. Symptoms may include redness and burning of skin. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, skin burns, and other skin damage.

Ingestion

ASHLAND

SAFETY DATA SHEET

Page: 2
Revision Date: 03/14/2011
Print Date: 3/16/2011
MSDS Number: R0171784
Version: 2.0

NAPA® PREM PERF UFMO SAE 15W40
MOTOR OIL
NP75128

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Skin, lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: acne, stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

Target Organs

No data

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Used motor oil has been shown to cause skin cancer in laboratory animals continually exposed by repeated applications. Avoid prolonged or repeated skin contact.

Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	CAS-No.	Concentration
HEAVY PARAFFINIC DISTILLATE	64742-54-7	>=80-<90%
ZINC COMPOUNDS	68649-42-3	>=1.5-<5%

NAPA® PREM PERF UFMO SAE 15W40
MOTOR OIL
NP75128

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, Carbon dioxide (CO₂), Water spray

NAPA® PREM PERF UFMO SAE 15W40
MOTOR OIL
NP75128

Hazardous combustion products

carbon dioxide and carbon monoxide, Hydrocarbons, hydrogen sulfide, zinc oxide, oxides of sulfur, nitrogen and phosphorus, Amines

Precautions for fire-fighting

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

Methods for cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Other information

Comply with all applicable federal, state, and local regulations.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

NAPA® PREM PERF UFMO SAE 15W40
MOTOR OIL
NP75128

Storage

Store in a cool, dry, ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

**HYDROTREATED PARAFFINIC DISTILLATE,
DEWAXED**

NIOSH	Recommended exposure limit (REL):	5 mg/m3	Mist.
NIOSH	Short term exposure limit	10 mg/m3	Mist.
OSHA Z1	Permissible exposure limit	5 mg/m3	Mist.
ACGIH	time weighted average	5 mg/m3	Inhalable fraction.

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist. Maintain eye wash station near work area.

Skin and body protection

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use. Wear resistant gloves (consult your safety equipment supplier).

Respiratory protection

NAPA® PREM PERF UFMO SAE 15W40
MOTOR OIL
NP75128

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	no data available
Colour	amber
Odour	hydrocarbon-like
Boiling point/boiling range	no data available
Melting point/range	no data available
Sublimation point	no data available
pH	no data available
Flash point	(>)390 °F / 199 °C Cleveland open cup
Ignition temperature	no data available
Evaporation rate	no data available
Lower explosion limit/Upper explosion limit	1 %(V) / 6 %(V)
Particle size	no data available
Vapour pressure	0.013 hPa @ 70.00 °F / 21.11 °C Calculated Vapor Pressure
Relative vapour density	no data available
Density	0.880 g/cm ³ @ 60.1 °F / 15.6 °C 7.4 lb/gal @ 60.1 °F / 15.6 °C
Bulk density	No data
Water solubility	negligible
Solubility(ies)	no data available
Partition coefficient: n-octanol/water	no data available
log Pow	no data available
Autoignition temperature	no data available
Viscosity, dynamic	no data available
Viscosity, kinematic	no data available
Solids in Solution	no data available
Decomposition temperature	no data available
Burning number	no data available
Dust explosion constant	no data available

ASHLAND
SAFETY DATA SHEET

Page: 7
Revision Date: 03/14/2011
Print Date: 3/16/2011
MSDS Number: R0171784
Version: 2.0

NAPA® PREM PERF UFMO SAE 15W40
MOTOR OIL
NP75128

Minimum ignition energy no data available

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to avoid

excessive heat

Incompatible products

Strong oxidizing agents

Hazardous decomposition products

carbon dioxide and carbon monoxide, Hydrocarbons

Hazardous reactions

Product will not undergo hazardous polymerization.

Thermal decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

HEAVY PARAFFINIC DISTILLATE : LD 50 Rat: > 15 g/kg

ZINC COMPOUNDS : LD 50 Rat: 2,000 - 5,000 mg/kg

Acute inhalation toxicity

HEAVY PARAFFINIC DISTILLATE : no data available

ZINC COMPOUNDS : no data available

Acute dermal toxicity

HEAVY PARAFFINIC DISTILLATE : LD 50 Rabbit: > 5 g/kg

ASHLAND
SAFETY DATA SHEET

Page: 8
Revision Date: 03/14/2011
Print Date: 3/16/2011
MSDS Number: R0171784
Version: 2.0

NAPA® PREM PERF UFMO SAE 15W40
MOTOR OIL
NP75128

ZINC COMPOUNDS : LD 50 Rabbit: > 2,000 mg/kg

12. ECOLOGICAL INFORMATION

Biodegradability

HEAVY PARAFFINIC DISTILLATE : no data available

ZINC COMPOUNDS : no data available

Bioaccumulation

HEAVY PARAFFINIC DISTILLATE : no data available

ZINC COMPOUNDS : no data available

Ecotoxicity effects

Toxicity to fish

HEAVY PARAFFINIC DISTILLATE : no data available

ZINC COMPOUNDS : no data available

Toxicity to daphnia and other aquatic invertebrates.

HEAVY PARAFFINIC DISTILLATE : no data available

ZINC COMPOUNDS : no data available

Toxicity to algae

HEAVY PARAFFINIC DISTILLATE : no data available

ZINC COMPOUNDS : no data available

Toxicity to bacteria

HEAVY PARAFFINIC DISTILLATE : no data available

ASHLAND
SAFETY DATA SHEET

Page: 9
Revision Date: 03/14/2011
Print Date: 3/16/2011
MSDS Number: R0171784
Version: 2.0

NAPA® PREM PERF UFMO SAE 15W40
MOTOR OIL
NP75128

ZINC COMPOUNDS : no data available

Biochemical Oxygen Demand (BOD)

HEAVY PARAFFINIC DISTILLATE : no data available

ZINC COMPOUNDS : no data available

Chemical Oxygen Demand (COD)

HEAVY PARAFFINIC DISTILLATE : no data available

ZINC COMPOUNDS : no data available

Additional ecological information

HEAVY PARAFFINIC DISTILLATE : no data available

ZINC COMPOUNDS : no data available

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT /LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	-----------------------------

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

ASHLAND
SAFETY DATA SHEET

Page: 10
Revision Date: 03/14/2011
Print Date: 3/16/2011
MSDS Number: R0171784
Version: 2.0

NAPA® PREM PERF UFMO SAE 15W40
MOTOR OIL
NP75128

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - ROAD

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

SARA Hazard Classification

ASHLAND
SAFETY DATA SHEET

Page: 11
Revision Date: 03/14/2011
Print Date: 3/16/2011
MSDS Number: R0171784
Version: 2.0

NAPA® PREM PERF UFMO SAE 15W40
MOTOR OIL
NP75128

Acute Health Hazard

SARA 313 Component(s)
ZINC COMPOUNDS

1.59 %

New Jersey RTK Label Information

HEAVY PARAFFINIC DISTILLATE 64742-54-7
LUBRICANT ADDITIVE
HYDROTREATED PARAFFINIC DISTILLATE, DEWAXED
ZINC COMPOUNDS
ZINC COMPOUNDS 68649-42-3

Pennsylvania RTK Label Information

HEAVY PARAFFINIC DISTILLATE 64742-54-7
LUBRICANT ADDITIVE
HYDROTREATED PARAFFINIC DISTILLATE, DEWAXED

Notification status

US. Toxic Substances Control Act y (positive listing)
Canada. Canadian Environmental Protection Act (CEPA). y (positive listing)
Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)
Australia. Industrial Chemical (Notification and Assessment) y (positive listing)
Act
New Zealand. Inventory of Chemicals (NZIoC), as published n (Negative listing)
by ERMA New Zealand
Japan. Kashin-Hou Law List n (Negative listing)
Korea. Toxic Chemical Control Law (TCCL) List y (positive listing)
Philippines. The Toxic Substances and Hazardous and Nuclear y (positive listing)
Waste Control Act
China. Inventory of Existing Chemical Substances y (positive listing)

Reportable quantity - Product

US. EPA CERCLA Hazardous Substances (40 CFR 302) 66666 lbs

Reportable quantity-Components

ARSENIC 7440-38-2 1 lbs

	HMIS	NFPA
Health	2	1

ASHLAND
SAFETY DATA SHEET

Page: 12
Revision Date: 03/14/2011
Print Date: 3/16/2011
MSDS Number: R0171784
Version: 2.0

NAPA® PREM PERF UFMO SAE 15W40
MOTOR OIL
NP75128

Flammability	1	1
Physical hazards	0	
Instability		0
Specific Hazard	--	--

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).