Supplier:
Permatex, Inc.
10 Columbus Blvd.
Hartford, CT 06106

Telephone: 1-87-Permatex

(877) 376-2839

## **Material Safety Data Sheet**

1. PRODUCT IDENTIFICATION

**Product Name:** 

765-1472 NAPA CLEAR RTV 110Z CQ

Item No:

21185

Product Type:

Silicone

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Percent	ACGIH 8 Hr. TWA:	OSHA 8 Hr. TWA:	
POLYDIMETHYLSILOXANE 63148-62-9	80-90			
SILICON DIOXIDE, AMORPHOUS 112945-52-5	1-10	10 mg/m3 TWA	6 mg/m3 TWA	
ETHYLTRIACETOXYSILANE 17689-77-9	1-10			
METHYLTRIACETOXYSILANE 4253-34-3	1-10			
ACETIC ACID % 64-19-7	***	10 ppm TWA; 25 mg/m3 TWA	10 ppm TWA; 25 mg/m3 TWA	

#### 3. HAZARDS IDENTIFICATION

Toxicity:

\*\*\*\*When this product is exposed to moisture, 1-3% acetic acid may be formed. May cause eye and skin irritation. May irritate lips, gums, tongue, mouth, nose and throat. May be harmful if swallowed. When heated to temperatures above 300 degrees F. in the presence of air, this product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Safe handling conditions may be maintained by keeping vapor concentrations below the OSHA permissible limit for formaldehyde.

Primary Routes of Entry:

Eye and skin contact, ingestion, inhalation.

Signs and Symptoms of Exposure:

Acetic acid produced during curing irritates eyes, nose and throat. Repeated skin contact may cause allergic skin reactions.

Ingredients	Percent	NTP:	ACGIH Carcinogens	IARC:
SILICON DIOXIDE, AMORPHOUS 112945-52-5	1-10	Group 2 - Reasonably anticipated		Amorphous Silica, Group 3: Vol. 68: 1997

Medical Conditions Recognized as Being Methyltriacetoxysilane: Eye, skin and pulmonary disorders. Aggravated by Exposure:

### 4. FIRST AID MEASURES

Ingestion: /

Skin Contact:

Rinse mouth with water several times. If swallowed, DO NOT induce vomiting. Keep individual calm.

Obtain medical attention.

If inhaled, remove from area to fresh air. Get medical attention if respiratory irritation develops or if

breathing becomes difficult.

Wipe off paste with paper towel or cloth. Wash exposed area with soap and water. Seek medical

attention if irritation persists.

Eye Contact: /

medical attention if irritation persists.

#### 5. FIRE FIGHTING MEASURES

Flash Point (°F/C):

More than 200 degrees F. Method: Tag Closed Cup

Product Name:

765-1472 NAPA CLEAR RTV 110Z CQ

Item No:

21185

Recommended Extinguishing Media:

Carbon Dioxide, Dry Chemicals, Foam.

Special Fire-Fighting Procedures:

Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

Hazardous Products Formed by Fire or

Formaldehyde, Silica fume, Acetic acid,

Thermal Decomposition:

Unusual Fire/Explosion Hazards:

None

Lower Explosive Limit:

Acetic acid: 4%

Upper Explosive Limit:

Acetic acid: 19.9% @ 200 degrees F.

# 6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:

Wipe or scrape up spill material. Maintain good ventilation for large spills. Place scrap material in a well-ventilated area and allow to cure to rubber. Clean up spills thoroughly as residue is slippery.

## 7. HANDLING AND STORAGE

Storage: Handling:

Store in a dry area below 90 degrees F. Keep container closed when not in use.

Avoid contact with skin and eyes. Do not inhale vapors. Do not wear contact lenses. Product releases acetic acid during application and curing. Wash hands before eating, drinking, chewing

gum, using tobacco or using the toilet.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:

Not normally required, but wearing safety glasses will minimize exposure.

Skin:

Rubber or plastic gloves

Ventilation:

General ventilation is usually adequate.

**Respiratory Protection:** 

Not normally necessary.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Clear paste

Odor:

ACETIC ACID ODOR

Boiling Point (°F):

Not applicable, polymeric material Does not apply

pH: Solubility in Water:

Polymerized

Specific Gravity:

1.01

VOC Content(Wt.%):

4.7% bt weight; 47.47 g/l

Vapor Pressure:

10 mm Hg @ 80 degrees F.

Vapor Density (Air=1):

Not Determined

## Evaporation Rate:

Not Determined

### 10. STABILITY AND REACTIVITY

**Chemical Stability:** 

Stable at normal conditions WILL NOT OCCUR

Hazardous Polymerization: Incompatabilities:

Polymerized by contact with moisture. Acetic acid liberated.

Conditions to Avoid:

Moisture while storing.

Hazardous Products Formed by Fire or

Formaldehyde, Silica fume, Acetic acid,

Thermal Decomposition:

#### 11. TOXICOLOGICAL INFORMATION

See Section 3

#### 12. ECOLOGICAL INFORMATION

No data available

### 13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal:

Disposal should be made in accordance with federal, state and local regulations.

**US EPA Waste Number:** 

NH - Not a RCRA Hazardous Waste Material

## 14. TRANSPORT INFORMATION

DOT (49CFR 172)

**Product Name:** 

**765-1472 NAPA CLEAR RTV 110Z CQ** 

Item No:

21185

Domestic Ground Transport

DOT Shipping Name:

Unrestricted

Hazard Class:

NONE

**UN/ID Number:** 

None

Marine Pollutant:

None

<u>IATA</u>

Proper Shipping Name:

Unrestricted

Class or Division:

None

**UN/NA Number: IMDG** 

NONE

**Proper Shipping:** Hazard Class:

Unrestricted

**UN Number:** 

None None

### 15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical

NONE

**CALIFORNIA PROP 65:** 

No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level.

TSCA Inventory Status:

All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating:

HEALTH 2, FLAMMABILITY 1, REACTIVITY 1

Estimated HMIS Classification:

FLAMMABILITY 1, REACTIVITY 1, HEALTH 2

NFPA is a registered trademark of the National Fire Protection Assn. HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By:

Denise Boyd

Health and Safety Manager

Company:

Permatex. Inc. 10 Columbus Blvd. Hartford, CT 06106

Telephone Number:

1-87-Permatex (877) 376-2839

Revision Date: 03/21/2001